

Gas electrovalves Elettrovalvole per gas

On request:

- N.O. Electrovalves
- 6 bar Electrovalves

Su richiesta:

- Elettrovalvole N.A.
- Elettrovalvole a 6 bar



Threaded normally-closed gas automatic solenoid valves - max working pressure 200 mbar
Elettrovalvole automatiche filettate a solenoide normalmente chiuse - max pressione di esercizio 200 mbar



ELV215220

code	type	tension	size	
ELV210220	EVO01	230 Vac	1/2"	<ul style="list-style-type: none"> • Brass body • CE homologation according to EN161 • Tensions on request: 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac • Flanged connections • normally open version
ELV215220	EVO02	230 Vac	3/4"	<ul style="list-style-type: none"> • Corpo ottone • Omologazione CE secondo EN161 • Tensioni su richiesta 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac • Attacchi flangiati • Versioni normalmente aperte
ELV220220	EVO03	230 Vac	1"	

Threaded normally-closed gas automatic solenoid valves - max working pressure 360 mbar
Elettrovalvole automatiche filettate a solenoide normalmente chiuse - max pressione di esercizio 360 mbar



ELV220230

Code	Type	Tension	Size	
ELV215230	EVP02	230 Vac	1/2"	<ul style="list-style-type: none"> • Aluminium body • CE homologation according to EN161 • Tensions on request: 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac • Flanged connections • normally open version
ELV220230	EVP03	230 Vac	3/4"	<ul style="list-style-type: none"> • Corpo alluminio • Omologazione CE secondo EN161 • Tensioni su richiesta 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac • Attacchi flangiati • Versioni normalmente aperte
ELV225230	EVP04	230 Vac	1"	

Manual reset, threaded, normally-closed gas solenoid valves - max working pressure 500 mbar
Elettrovalvole a riarmo manuale filettate a solenoide normalmente chiuse - max pressione di esercizio 500 mbar



ELV215240

Code	Type	Tension	Size	
ELV215240	COP02	230 Vac	1/2"	<ul style="list-style-type: none"> • Brass body • CE homologation according to EN161 • Tensions on request: 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac • Flanged connections • normally open version
ELV220240	COP03	230 Vac	3/4"	<ul style="list-style-type: none"> • Corpo ottone • Omologazione CE secondo EN161 • Tensioni su richiesta 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac • Attacchi flangiati • Versioni normalmente aperte

GAS VALVES

Gas elctrovalve

Elettrovalvole per gas

Manual reset, threaded, normally-closed gas solenoid valves - max working pressure 500 mbar

Elettrovalvole a riarmo manuale filettate a solenoide normalmente chiuse - max pressione di esercizio 500 mbar

- Aluminium / brass body
- CE homologation according to EN161
- Tensions on request: 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac
- Flanged connections
- normally open version
- On request: 6 bar working pressure

- Corpo alluminio / ottone
- Omologazione CE secondo EN161
- Tensioni su richiesta 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac
- Attacchi flangiati
- Versioni normalmente aperte
- Su richiesta: pressione esercizio 6 bar



ELV240210



ELV220200

code	type	tension	size	body
ELV215200	CO02C	230 Vac	1/2"	ottone / brass
ELV220200	CO03C	230 Vac	3/4"	ottone / brass
ELV225200	CO04C	230 Vac	1"	ottone / brass
ELV220210	CM03C	230 Vac	3/4"	alluminium
ELV225210	CM04C	230 Vac	1"	alluminium
ELV232210	CM05C	230 Vac	1 1/4"	alluminium
ELV240210	CM06C	230 Vac	1 1/2"	alluminium
ELV250210	CM07C	230 Vac	2"	alluminium

Manual reset, flanged, normally-closed gas solenoid valves - max working pressure 500 mbar

Elettrovalvole a riarmo manuale flangiata a solenoide normalmente chiuse - max pressione di esercizio 500 mbar

- Aluminium body
- CE homologation according to EN161
- Tensions on request: 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac
- Flanged connections
- normally open version
- On request: 6 bar working pressure

- Corpo alluminio
- Omologazione CE secondo EN161
- Tensioni su richiesta 12 Vdc, 12 Vac, 24 Vdc, 24 Vac, 110 Vac
- Attacchi flangiati
- Versioni normalmente aperte
- Su richiesta: pressione esercizio 6 bar



ELV291212



ELV265212

code	type	tension	size
ELV225212	CM25C	230 Vac	DN 25
ELV232212	CM32C	230 Vac	DN 32
ELV240212	CM40C	230 Vac	DN 40
ELV250212	CM50C	230 Vac	DN 50
ELV265212	CX08C	230 Vac	DN 65
ELV280212	CX09C	230 Vac	DN 80
ELV285212	CX10C	230 Vac	DN 100
ELV287212	CX11C	230 Vac	DN 125
ELV289212	CX12C	230 Vac	DN 150
ELV291212	CX13C	230 Vac	DN 200